



Professional Grade Oil & Grease Remover

for Pavers and Slabs



UPDATE

July 7, 2010

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Sealed or bare surfaces
- Pavers and slabs made of concrete or natural stone, poured or stamped concrete, masonry, etc.
- Driveways, pool decks, patios, terraces, commercial parking lots, pedestrian areas, etc.

PROPERTIES

- Removes penetrated petroleum-based products
- Dislodges and encapsulates oil and grease
- Dries from a liquid to a powder
- No scrubbing. No rinsing. No mess

DESCRIPTION

PROFESSIONAL GRADE OIL & GREASE REMOVER is an industrial strength petroleum-based product remover. It lifts and absorbs embedded oil and grease stains as it dries from a liquid to a powder. Specially formulated for concrete pavers, slabs and walls, natural stone, poured or stamped concrete, etc., TECHNISEAL® PROFESSIONAL GRADE OIL & GREASE REMOVER works without damaging or discoloring the material and is easy to use.

DIRECTIONS

Wear adequate protective clothing. **To ensure the results will meet your expectations, always test the product on a small hidden area.**

Do not use on asphalt.

For best results, use when temperature is above 60°F and provide maximum ventilation.

Application:

- 1) Apply a generous amount of product to an oil or grease stain and let sit until product has turned to powder. With temperature above 60°F and good ventilation, this process should take between 5 and 8 hours. Process is slowed down and may be inhibited in lower temperatures.
- 2) When the product has completely dried to a powder, sweep up with a broom and dispose of the powder.

Note: surface may still appear dark immediately after powder is swept up. This is not oil; it is moisture trapped in the pores. It should evaporate within a few hours or days.

STORAGE and SHELF LIFE

Product must be kept in its original, unopened and tightly sealed container and stored in a dry and well ventilated place with controlled temperature (40°F to 75°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is at least 2 years following production (see date on packaging).

PACKAGING

Product Code	Retail Size	Units per box	Boxes per pallet
121-591	1 qt.	6	100

WARNING

Keep away from heat, sparks and flame. Do not breathe vapor or mist. Do not get on skin or clothing. Avoid contact with eyes. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. **Keep out of reach of children.**

FIRST AID TREATMENT - Inhalation: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately. **Ingestion:** Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately. **Eye contact:** Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately. **Skin contact:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

FOR MORE INFORMATION, CONSULT THE MATERIAL SAFETY DATA SHEET

SHIPPING

Land and sea

Flammable liquid

Class: 3

UN Number: NA1993

Packing Group: III

LIMITED WARRANTY

Since it has no control over surface preparation and product application, Techniseal® can not guarantee the results. Techniseal warranty is limited to the replacement of product. A proof of purchase will be required for any claim. Note: User should have an up-to-date technical data sheet handy (techniseal.com) and make sure that this product meets his or her needs by carrying out a test under anticipated conditions of use.