



COLOR BOOST

PAVER PROTECTOR (WLP)



UPDATE

February 4, 2011

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Recommended for pool decks, patios, walkways and retaining walls

PROPERTIES

- Enhances paver color
- Penetrating. Will not make surface more slippery
- Solvent-based

DESCRIPTION

COLOR BOOST PAVER PROTECTOR (WLP) from TECHNISEAL® is a high-tech matte-finish penetrating protective sealant that provides color enhancement to porous pavers. COLOR BOOST PAVER PROTECTOR also acts as an oil repellent, making cleaning easier by preventing oil, grease (barbecue) and dirt from penetrating the material. As a water repellent, it helps prevent the appearance of mold and protects against water damage. Easy to apply, it provides maximum effectiveness and durability. Non-film-forming, COLOR BOOST PAVER PROTECTOR will not make surfaces more slippery and hence is ideal for protecting pool decks, patios, steps, walkways, etc. It is also ideal for retaining walls.

DIRECTIONS

BEFORE YOU BEGIN:

Wear adequate protective clothing.

ALWAYS TEST the product on a small hidden area of approximately 4 sq. ft. and wait 48 hours to ensure the results will meet your expectations.

This product chemically bonds to the substrate, **it CANNOT be removed.**

Do not thin or dilute.

DO NOT apply to natural stones, poured concrete and wet-cast or clay pavers.

Apply only to bare material or to material that has been previously sealed with this product.

New concrete pavers: Efflorescence (whitish salt) may appear on concrete pavers within 60 days following installation. It is suggested to wait at least 60 days before cleaning and sealing. Applying a PROTECTOR before 60 days may cause blotchiness of the surface.

Newly installed polymeric sand on older pavers: Wait at least 30 days before cleaning and sealing pavers.

Recoating: Wait at least 3 to 5 years (depending on surface wear) and prime surface as indicated on this label before recoating.

Light-grey pavers: These types of surfaces may show uneven color shading after application of a PROTECTOR that offers color enhancement. Always test a small section of pavers to ensure the results meet the desired aesthetic. Results will vary according to paver type, porosity and color. Proper surface priming is essential.

APPLICATION:

Surface must be clean, dry (24 hours without precipitation) and warm to the touch (morning). Joints must also be dry. Temperature must be between 50°F and 80°F, and rain should not be forecasted over the following 24 hours. Sprinklers must be shut off. For optimal results, apply product under constant weather conditions and using the same application method from start to finish. Shake container or stir product before use.

Roller application: Using a TECHNISEAL® SLIT FOAM ROLLER (19 mm) and a metal paint tray, apply a first coat of PROTECTOR to saturation.

Sprayer application: Soak the surface using an airless or pump sprayer.

Wait until surface is dry to the touch and immediately apply a second coat. As each coat is being applied, remove any excess of PROTECTOR with a clean and dry foam roller or mop, before it dries. Leaving excess PROTECTOR on the surface may cause blotchiness on the surface, which is IRREVERSIBLE and PERMANENT. Do not apply more than 2 coats. Stepping on freshly applied PROTECTOR will leave PERMANENT marks on pavers.

Let dry for 24 hours before walking on the surface and 48 hours before allowing traffic.

Cleaning of tools: Use lacquer thinner.

COVERAGE

1 gal. covers up to 120 sq. ft. for a two-coat application. Coverage will depend on surface porosity and joint width. Cleaning yearly with TECHNISEAL® HC HARDSCAPE CLEANER will keep pavers looking fresh.

STORAGE and SHELF LIFE

Keep sheltered from weather and direct sunlight. The shelf life is minimum 1 year if the product is kept in its original, unopened and tightly sealed container, and stored in a dry, cool and well ventilated area (between 50 and 70°F).

PACKAGING

Product Code	Pro Size	Units per box	Units per pallet
121-293	1 gal.	4	180
121-296	5 gal.	—	48
221-298	55 gal.	—	4

WARNING

Contains Aromatic Petroleum Naphtha 64742-95-6, Proprietary Solvent and Silanes. Keep away from heat, sparks and flames. Do not smoke while using. Avoid breathing vapors. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wash thoroughly after handling. Keep container closed when not in use. **KEEP OUT OF REACH OF CHILDREN. FIRST AID: Eye Contact:** Immediately flush eyes with water for at least 15 minutes and call a physician. **Skin Contact:** Wash thoroughly with soap and water. Get medical attention if irritation persists. **Inhalation:** Move to fresh air. Get medical attention if irritation or other symptoms develop and persist. **Ingestion:** Do Not induce vomiting. Immediately call a physician or poison control center. **Warning:** This product contains chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. VOC (Less Exempt Solvent and Water): <400 g/L FOR MORE INFORMATION, CONSULT THE MATERIAL SAFETY DATA SHEET

SHIPPING

Land and sea

NOT REGULATED

LIMITED WARRANTY

Manufacturer, having no control over the use of the materials, does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq.ft. (0.4 m²). This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty made above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods and implied warranty of fitness of goods for any particular purpose.