



PR Paver Restorer

for Pavers and Slabs

UPDATE

April 27, 2010

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Bare surfaces
- Concrete or clay pavers and slabs

PROPERTIES

- Removes cement slurry, jointing sand haze and stains generated by paver cuts

DESCRIPTION

TECHNISEAL® PR PAVER RESTORER FOR PAVERS AND SLABS is the most effective product available for removing cement slurry and jointing sand haze on concrete or clay pavers and slabs.

DIRECTIONS

Wear adequate protective clothing (acid-resistant) to prevent eye and skin contact including, boots, impervious gloves, safety goggles and respirator (if needed). Wear adequate protective clothing. **To ensure the results will meet your expectations, always test the product on a small hidden area of approximately 4 sq. ft.**

WARNING - DO NOT USE FULL STRENGTH. ALWAYS DILUTE PRODUCT.

Dilution:

Principle: To use the strongest concentration of product without etching or discoloring pavers. A weaker concentration will increase the labor factor.

1. Into a plastic watering can or using a professional spraying system (no metal parts), dilute 1 part product in 1 part water.
2. Test the concentration on spare pavers or on a small hidden area. Test area or spare pavers must be humid.
 - If the product etches or discolors the pavers: lower the concentration (1 part product in 2 parts water) until the product no longer etches or discolors the pavers.
 - If the product DOES NOT etch or discolor the pavers: you may use a stronger concentration of 1 part product for 1/2 part water. This will increase product efficiency and reduce scrubbing, . The concentration must be strong enough to remove haze without etching or discoloring pavers.

IMPORTANT: Always test diluted product before using on the entire surface.

Wetting:

To prevent product penetration and make rinsing easier, first saturate surface with water. As soon as the surface starts to dry, apply the product as described next.

Application:

Product should not sit on the surface more than a few seconds.

1. If application is done on pavers with new polymeric sand joints, wait 30 days before applying the product.
2. Work in small sections; no more than 100 sq. ft.
3. Using a plastic watering can or a professional spraying system (no metal parts), cover the area with product.
4. Lightly scrub.
5. Rinse immediately and thoroughly.
6. Move on to the next section. **Product should not sit on the surface more than a few seconds.**

IMPORTANT: DO NOT let product dry on the surface. If product dries on the surface, reapply product, lightly scrub and rinse immediately and thoroughly.

TIP: To improve efficiency on large areas, 3 persons are recommended to apply the product. One person should spray (pour) the product while another is scrubbing and a third is rinsing.

IMPORTANT

It is the responsibility of the user to know and follow all approved safety procedures and to comply with all applicable federal, state, and local laws, regulations and ordinances. Never use this product without first consulting with local authorities regarding the application of chemical products, waste management and run-offs.

WARNING

DANGER. CAUSES RESPIRATORY TRACT, EYE, AND SKIN BURNS. MAY BE HARMFUL IF SWALLOWED. Do not breathe vapor or mist. Do not ingest. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure. **KEEP OUT OF REACH OF CHILDREN. FIRST AID: Eye contact:** Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately. **Skin contact:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately. **Inhalation:** Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately. **Ingestion:** Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

FOR PROFESSIONAL USE ONLY.

FOR MORE INFORMATION, CONSULT THE MATERIAL SAFETY DATA SHEET.

SHIPPING**Land and sea**

Class: 8
UN Number: 3265
Packing Group: III
Flash Point: n/a

LIMITED WARRANTY

LIMITED WARRANTY: Manufacturer, having no control over the use of the materials, does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq.ft. (0.4 m²). This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty made above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods and implied warranty of fitness of goods for any particular purpose.