



Rust Remover for Pavers and Slabs



UPDATE

July 30, 2008

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Sealed or bare surfaces
- Pavers and slabs made of concrete
- Driveways, pool decks, patios, terraces, commercial parking lots, pedestrian areas, etc.

PROPERTIES

- Effectively removes stains caused by metal, rusted water, fertilizer, etc.

DESCRIPTION

TECHNISEAL RUST REMOVER FOR PAVERS AND SLABS takes out rust from pavers and slabs made of concrete. It effectively dissolves stains caused by rusted metal, fertilizer granules¹, etc. Since it contains no hydrochloric (muriatic) acid, it won't damage the pavers.

¹To remove fertilizer stains from a large surface, it is recommended to use TECHNISEAL EFFLORESCENCE CLEANER (121-533).

DIRECTIONS

Wear adequate protective clothing. **To ensure the results will meet your expectations, it is advisable to test the product on a small hidden area.**

Wear rubber gloves and safety goggles. Wet the stain and cover it generously with RUST REMOVER; using a SMALL TECHNISEAL BRUSH, scrub the stain until dissolved; rinse immediately with water. If rust persists, repeat the operation.

Important: Pavement with efflorescence (whitish salt) will appear spotted after the use of RUST REMOVER; for uniform results, finish by cleaning the entire surface with EFFLORESCENCE CLEANER (121-533). Rust streaks left by metal snowploughs may be difficult to remove. **Do not** use on natural stones or poured concrete.

STORAGE and SHELF LIFE

Product must be kept in its original, unopened and tightly sealed container and stored in a dry and well ventilated place with controlled temperature (40°F to 75°F). Keep sheltered from weather and direct sunlight. Properly stored, the product's shelf life is 3 years following production (see date on packaging).

PACKAGING

Product Code	Retail Size	Units per box	Units per pallet
121-521	1 qt.	6	720

WARNING

DANGER. CORROSIVE. CAUSES IRREVERSIBLE EYE AND SKIN DAMAGE. VAPOR EXTREMELY IRRITATING. MAY CAUSE DELAYED LUNG INJURY. HARMFUL IF SWALLOWED. **CONTAINS:** Phosphoric acid. Do not get in eyes, on skin or on clothing. Avoid breathing vapor or mist. Do not take internally. Use only with adequate ventilation. Keep container closed when not in use. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** In case of contact: immediately flush eyes with plenty of water for at least 15 minutes; immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. If inhaled, remove to fresh air. If not breathing, give artificial respiration and get medical attention. Wash contaminated clothing and thoroughly clean contaminated shoes before reuse. If swallowed, get medical attention immediately. Do not induce vomiting unless directed to do so by medical personnel. Calculated VOC: 0 g/L.

FOR MORE INFORMATION, CONSULT THE MATERIAL SAFETY DATA SHEET

SHIPPING

Land and sea

NOT REGULATED

Phosphoric Acid in Solution

Class: 8 (9.2)

UN Number: 1805

Packing Group: III

(Flash Point: n/a)

LIMITED WARRANTY

Since it has no control over surface preparation and product application, Techniseal can not guarantee the results. Techniseal warranty is limited to the replacement of product proven defective. A proof of purchase will be required for any claim. Note: User should have an up-to-date technical data sheet handy (techniseal.com) and make sure that this product meets his or her needs by carrying out a test under anticipated conditions of use.