



WET LOOK

Paver Protector (WLSC)



UPDATE

February 8, 2011

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Recommended for driveways, parking lots, patios and walkways

PROPERTIES

- Enhances paver color
- Optimal oil repellency
- Solvent-based

DESCRIPTION

Made of acrylic and plasticizers, TECHNISEAL[®] WET-LOOK PAVER PROTECTOR (WLSC) is a low-solid, wet-look microporous transparent coating that protects pavers made of concrete while enhancing their original color. It reduces oil and dirt penetration, and makes cleaning easier. Easy to apply, it penetrates the surface for maximum adhesion and durability. WET-LOOK PAVER PROTECTOR will not peel or discolor. It resists the elements (freeze-thaw cycles, sun, rain, etc.), as well as calcium and salt. It also resists hot tire pick-up.

DIRECTIONS

BEFORE YOU BEGIN:

Wear adequate protective clothing. **ALWAYS TEST the product on a small hidden area of approximately 4 sq. ft. to ensure the results will meet your expectations. Do not thin or dilute.**

Apply only to bare material or to material that has been previously sealed with this product.

Recoating: Wait until the surface of the PROTECTOR is worn before recoating (minimum of 2 years).

Avoid product build-up: Excess recoating may eventually lead to whitening of the surface.

New concrete pavers: Efflorescence (whitish salt) may appear on concrete pavers within 60 days following installation. **Wait at least 60 days** before cleaning and sealing. Applying a PROTECTOR before 60 days may cause blotchiness of the surface.

Newly installed polymeric sand: **Wait at least 30 days** before cleaning and sealing pavers.

Light-grey pavers: These types of surfaces may show uneven color shading after application of a WET-LOOK PROTECTOR. Always test a small section of pavers to ensure the results meet the desired aesthetic.

Slipperiness: This product can make the surface more slippery when wet. The application of a matte-finish PROTECTOR such as the COLOR BOOST (WLP) is recommended where slipperiness represents a cause for concern.

Results will vary according to paver type, porosity and color. Proper surface priming is essential.

PREPARATION:

Stain removal: If necessary, remove any stains (oil, rust, etc.) from the surface using the appropriate TECHNISEAL® stain remover.

Priming: This step is essential to obtain an optimal and uniform gloss-finish. Prime the entire surface by removing all efflorescence and ground-in dirt. This ensures a uniform look and allows the PROTECTOR to better penetrate the surface. Use TECHNISEAL® PAVER PRIMER/EFFLORESCENCE CLEANER for pavers with efflorescence or pavers less than 5 years old. Use Techniseal® HC HARDSCAPE CLEANER for surfaces without efflorescence or pavers more than 5 years old.

Proper rinsing is essential.

APPLICATION:

Surface must be clean, dry (24 hours without precipitation) and warm to the touch (morning). Joints must also be dry. Temperature must be between 50°F and 80°F, and rain should not be forecasted over the following 24 hours. Sprinklers must be shut off. For optimal results, apply product under constant weather conditions and using the same application method from start to finish. Shake container or stir product before use.

Roller application: Using a TECHNISEAL® SLIT FOAM ROLLER (19 mm) and a metal paint tray, saturate the surface with a single coat of PROTECTOR.

Sprayer application: Soak the surface using an airless or pump sprayer.

Once a section of approximately 150 sq. ft. has been rolled or sprayed, **back-roll** any excess PROTECTOR with a foam roller, before it dries.

On a bare surface, apply a second coat as soon as the surface is dry to the touch.

On a previously sealed surface or to obtain a less vibrant wet-look on a bare surface, apply **only one coat to saturation**. The level of saturation obtained will determine the intensity of the gloss-finish.

Let dry for 24 hours before walking on the surface and 48 hours before allowing traffic.

Cleaning of tools: Use lacquer thinner.

COVERAGE

1 gal. covers up to 150 sq. ft. per coat. Coverage will depend on surface porosity and joint width. Second coat will take less product.

Cleaning yearly with TECHNISEAL® HC HARDSCAPE CLEANER will keep pavers looking fresh.

STORAGE and SHELF LIFE

Product must be kept in its original, unopened and tightly sealed container, and stored in a dry and well ventilated place with controlled temperature (40°F to 75°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product’s shelf life is 3 years following production (see date on packaging).

PACKAGING

Product Code	Pro Size	Units per box	Units per pallet
121-013	1 gal.	4	180
121-016	5 gal.	—	48
221-018	55 gal.	—	4

WARNING

Contains Aromatic Petroleum Naphtha 64742-95-6, 4-Chlorobenzotrifluoride 98-56-6, Proprietary Solvent, Benzyl Butyl Phthalate 85-68-7 and Proprietary Polymer. Keep away from heat, sparks and flames. Do not smoke while using. Avoid breathing vapors. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wash thoroughly after handling. Keep container closed when not in use. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** **Eye Contact:** Immediately flush eyes with water for at least 15 minutes and call a physician. **Skin Contact:** Wash thoroughly with soap and water. Get medical attention if irritation persists. **Inhalation:** Move to fresh air. Get medical attention if irritation or other symptoms develop and persist. **Ingestion:** Do not induce vomiting. Immediately call a physician or poison control center. **WARNING:** This product contains chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. VOC (Low solids calculation): <120 g/L

SHIPPING

Land and sea: NOT REGULATED

Packing Group: III

(Flash Point: > 100°F)

Small means of containment: ≤ 100 gal.

LIMITED WARRANTY

Manufacturer, having no control over the use of the materials, does not guarantee finished work. Replacement of any defective product shall be the buyers sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq.ft. This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty made above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods and implied warranty of fitness of goods for any particular purpose.